



HEATER SLIDES  
FROM BOTTOM  
TO TOP!

### STANDARD FEATURES

- "SLIDE" 1.375/5.5KW, 15" Heater Assembly
- All Circuits Convertible to 120 or 240VAC
- Installation Kit (see below)
- SMART-ECON Economy Mode Settings
- SMART-FREEZE Protection
- "VDS" Visual Diagnostics
- Lighted SMART Cords
- "Paint-Lock" Rust Proof Enclosure
- Heater "ON" Indicator Light
- Detailed Owners Manual & Wiring Diagram

### OPTIONS

- Versi-Heat Remote Heater with 60" Cord
- Less Heater Unit
- IR Remote Control Kit
- Auxiliary Spaside

"SLIDE" HEATER FEATURE!

Gecko™ Series

### SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL

Model	Pump 1	Pump 2	Pump 3	Blower	Aux Circuit	Ozone	Circ Pump	12V Light	H/C GFCI
CS9709-US	1 or 2 SPD	1 or 2 SPD	1 SPD	1-3 SPD	2	YES	YES	1-3 STEP	NO
CS9709-US-HC	1 or 2 SPD	1 or 2 SPD	1 SPD	1-3 SPD	2	YES	YES	1-3 STEP	YES

### SPASIDE OPTIONS

### INSTALLATION KIT (Included)



Auxiliary Spaside  
HQ PT#: 34-0210  
5"L x 2.5"H



HTII 10 Button Spaside  
(Included)  
HQ PT#: 34-0190A  
7"L x 3.25"H



IR Remote Kit  
HQ PT#: 48-0196A-6

#### Kit Includes:

- Spaside Control
- Spaside Adapter Plate
- Component Cords
- 2" Tailpieces w/Gaskets
- 12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

### REPLACEMENT PARTS FOR CS9700 SOLID STATE SERIES

Model	Circuit Board	Spaside	Temp Sensor	Hi-Limit Sensor	Heater Element (5.5kW)	PSI Switch	Heater Assy (15")
CS9709-US/HC	33-0025-R8	34-0190A	34-0203D-36	34-0201D-36	12-0100-K	34-0178A	22-87B-S00-1FP3

For a complete list of parts, refer to our Parts Catalog

### SYSTEM SPECIFICATIONS

**ELECTRICAL INPUT SPECIFICATION:** SINGLE PHASE, 120/240VAC, 60HZ

**SYSTEM DIMENSIONS:**

15"W x 14"H x 6"D

**ELECTRICAL OUTPUT SPECIFICATION:**

**SHIPPING WEIGHT:**

23 LBS

CIRCUIT(S)	MAXIMUM AMPS
PUMP(S)	13A
BLOWER	8A
OZONE	2A
CIRCULATION PUMP	5A
12V LIGHT	1A
HEATER	23A

**PACKAGING / SHIPPING :**

INDIVIDUAL (HQ STOCK)  
FOB CORONA, CA 92880