

HEATER SLIDES FROM BOTTOM TO TOP!

"SLIDE" HEATER FEATURE!



Balboa® Series

STANDARD FEATURES

- M7® Technology Equipped
- "SLIDE" 1.325/5.5kW, 15" Heater Assembly
- Spaside Control
- All Circuits Convertible to 120 or 240VAC
- 12V Light Assembly
- Freeze Protection
- Standard, Economy & Sleep Modes
- Lighted Smart Cords
- Easy To Install & Service
- Installation Kit (see below)
- Detailed Owners Manual & Wiring Diagram
- US and Canada UL Recognized

OPTIONS

- Versi-Heat Remote Heater with 60" Cords
- Various Heater Wattages
- Wireless Remote Control
- Less Heater Unit

SUPPORTED PERIPHERALS AND CIRCUITS BY MODEL							
Spaside Control	Model	Platform	Pump 1	Pump 2	Blower	Circ Pump	Heater
 ECO-200 Series 4.3"L x 1.6"H	CS6109B-US	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
	CS6209B-US	VS501Z	2 SPD	1 SPD** OR BLOWER**	N/A	YES	5.5kW
	CS6229B-US	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
	CS6239B-US*	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW
 ECO-401 Series 6.3"L x 2.2"H	CS6109B-US-F	VS500Z	2 SPD	N/A	N/A	YES	5.5kW
	CS6209B-US-F	VS501Z	2 SPD	1 SPD** OR BLOWER**	N/A	YES	5.5kW
	CS6229B-US-F	VS511Z	2 SPD	2 SPD	N/A	YES	5.5kW
	CS6239B-US-F*	VS513Z/510Z	2 SPD	1 SPD	1 SPD (12A)	YES	5.5kW

*Pump 2 & Blower button work in sequence ** Pump 2 OR Blower

WIRELESS I/R REMOTE KIT

Kit Includes:

- Remote Control
- I/R Receiver Sensor (7')



Wireless I/R Remote Kit
HQ PT#: 48-0197
(parts available separately)

INSTALLATION KIT (Included)

Kit Includes:

- Spaside Control (See Above)
- Spaside Adapter Plate
- Component Cords
- 2" Tailpieces w/Gaskets
- 12V Light Assembly



All Hydro-Quip control systems include a spaside as standard. If an optional spaside is desired, please contact your Hydro-Quip representative for more details.

REPLACEMENT PARTS FOR CS6000B SOLID STATE SERIES						
Model	Circuit Board	Spaside	M7® Sensors (46")	Heater Element (5.5kW)	Heater Assy (15")	
CS6109B-US	33-0032A	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6209B-US	33-0032B	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6229B-US	33-0032C	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6239B-US	33-0032D	34-0225-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6109B-US-F	33-0032A	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6209B-US-F	33-0032B	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6229B-US-F	33-0032C	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	
CS6239B-US-F	33-0032D	34-0226-U	34-0202B (x2)	12-0100-K	22-87M-S00-1F03	

For a complete list of parts, refer to our Parts Catalog

SYSTEM SPECIFICATIONS		
ELECTRICAL INPUT SPECIFICATION:	SINGLE PHASE, 120/240VAC, 60HZ	FLOW RATE: 23 GPM Min.
ELECTRICAL OUTPUT SPECIFICATION:		SYSTEM DIMENSIONS: 15"W x 11"H x 6"D
CIRCUIT(S)	MAXIMUM AMPS	SHIPPING WEIGHT: 18 LBS
PUMP(S)	12A	PACKAGING / SHIPPING : INDIVIDUAL (HQ STOCK)
BLOWER	12A	FOB CORONA, CA 92880
OZONE	1A	
CIRCULATION PUMP	4A	
12V LIGHT	1A	
HEATER	23A	